

EXPECTED DELIVERABLES (from successful bidder)

- The Bidder has to specify the Name of the OEMs with the product name in the Technical specification.
- The servers' hardware configuration has to be done by the bidder. The hardware should not have any single point of failure.
- The Bidder should provide external backup solution for the proposed setup .The backup has to be stored encrypted in AES-128/SHA-256 format.
- The backup taken should be AES128/SHA-256 encrypted.
- The vendor has to quote two different OEMs for the Perimeter and Core Segment. The vendor has to quote the same OEM for all requirements at the perimeter and all requirements at the core.

S N	Description	No. of Users	Qty
1	Perimeter Firewall Appliances for Data Center (DC) as per Technical Specifications	Unlimited	02
2	Perimeter Firewall Appliances for DR site as per Technical Specifications	Unlimited	02
3	Perimeter Firewall Appliances at IDC as per Technical Specifications	Unlimited	02
4	Perimeter Firewall Appliances at Yogakshema as per Technical Specifications	Unlimited	02
5	Core Firewall Appliances for Data Center (DC) and DR site as per Technical Specifications	Unlimited	04
6	Core Firewall Appliances for IDC & Yogakshema as per Technical Specifications.	Unlimited	04
7	Dedicated APT/Sandbox appliance at all locations as per technical specifications	NA	
7	Servers for Management with Logging and Reporting of Firewalls to provide high-availability provision at 2 different locations (DC and DR) to take care of the management of firewalls at all sites. It is the responsibility of vendor to do proper hardware sizing to avoid any bottlenecks. Vendor to factor Hardware, Software with necessary storage, RAID, any licenses (OS, database etc.). They should not depend on LIC for any provisioning in this regard.	2 Locations	02
8	Direct Premium Support with 24x7x365 with OEM. Vendor to provide this Support for all of above components	Not Applicable	
9	On-site Support of L1 & L2 personnel at Mumbai		1 Each
10	On-site support of L1 at Bengaluru		1
11	Offsite Support of L1 Engineer after LIC's office hours		1
12	Offsite L3 Engineer		1
13	KVM switches It should be suitable for placing 8 Servers / appliances. KVM SWITCH should have following specifications – 8 port integrated LCD, with full set of cables, 17" TFT LCD panel, and Key board in notebook form factor with PS2/USB interface.		6
14	Half Yearly OEM Audit Report		
15	Backup Solution as per technical specification		

